

RECEIVED  
CENTRAL FAX CENTER

Serial No. 10/693,624  
Docket No. 062004-1791

OCT 12 2006

AMENDMENTS

Please amend the application as indicated hereafter.

In the Claims

Please amend the claims as indicated below. The language being added is underlined ("\_\_\_") and the language being deleted contains strikethrough ("—"):

1. (Currently Amended) An apparatus for determining in situ pore fluid and soil properties, the apparatus comprising:

a penetrating tip member configured to penetrate the soil; and  
an attachment module coupled to the penetrating tip member, the attachment module including at least one mandrel, each mandrel including at least one piezo sensor and a friction sleeve,

wherein each piezo sensor is capable of obtaining an in situ measurement of pore pressure at a location corresponding proximal to the at least one mandrel on the attachment module, each friction sleeve of the respective mandrel having surface texture of a particular roughness that is capable of inducing an internal shearing of the soil, each piezo sensor of the respective mandrel being capable of measuring in situ pore fluid pressure from the induced shearing of the soil generated by the friction sleeve of the respective ~~mandrel~~ mandrel.

wherein the attachment module further comprises at least one load cell, the load cell being coupled in sequence to the mandrel.

wherein the at least one load cell obtains an in situ measurement of interface strength at a depth that is proximal to the location of the at least one load cell.

2. (Original) The apparatus of claim 1, wherein the attachment module further comprises a hollow inner chamber for containing data and power components.

Serial No. 10/693,624  
Docket No. 062004-1791

3. (Original) The apparatus of claim 1, wherein the penetrating tip member further comprises a conventional cone penetration testing (CPT) module.
4. (Canceled)
5. (Currently Amended) The apparatus of claim [4] 1, wherein the at least one piezo sensor is coupled adjacent to at least one load cell, the at least one piezo sensor being isolated to measure the pore fluid pressure generated for the at least one load cell, wherein a friction sleeve associated with the at least one load cell induces an internal shearing of the soil which enables the piezo sensor to measure pore fluid pressure.
6. (Currently Amended) The apparatus of claim [4] 1, wherein each load cell further comprises a friction sleeve configured with a surface texture, where the surface texture has a corresponding surface roughness value;  
wherein each surface texture for a selected friction sleeve is configured to induce internal shearing of the soil as the attachment module penetrates the soil and to be self-cleaning, such that soil particles do not adhere to a surface of the friction sleeve.
7. (Previously Presented) The apparatus of claim 6, wherein the attachment module comprises multiple load cells, each load cell having a friction sleeve, the attachment module further comprising a vertical arrangement of the friction sleeves in ascending order according to increasing roughness of the surface texture, such that the least rough friction sleeve is placed closest to the penetrating tip member and the roughest friction sleeve is placed furthest away from the penetrating tip member.
8. (Original) The apparatus of claim 1, wherein the at least one piezo sensor produces a signal at a corresponding depth in a single sounding, and the signals correspond to individual in situ measurements of pore fluid pressure at the corresponding depth.

Serial No. 10/693,624  
Docket No. 062004-1791

9. (Original) The apparatus of claim 1, wherein pore fluid pressure measurements from the attachment module are transmitted to a data acquisition system.
10. (Previously Presented) The apparatus of claim 6, wherein the friction sleeve of each load cell has an average surface roughness of approximately 0.05 to approximately 250  $\mu\text{m}$ .
11. (Previously Presented) The apparatus of claim 6, wherein each friction sleeve comprises a surface texture that is characterized by geometric parameters, including height, diagonal spacing, penetration angle, and width.
12. (Original) The apparatus of claim 11, wherein the geometric parameters of each of the surface textures comprise height variations from approximately 0.25 mm to approximately 2.0 mm, diagonal spacing from approximately 4.6 mm to approximately 12.5 mm, and penetration angles from approximately 30 degrees to approximately 120 degrees.
13. (Original) The apparatus of claim 3, further comprising a data acquisition system, the data acquisition system comprises:
- means for measuring penetration depth of the penetrating tip member and the attachment module;
  - means for obtaining penetrating tip member measurement values;
  - means for measuring verticality of the penetrating tip member; and
  - means for obtaining pore fluid pressure values at each measurement increment on each piezo sensor located in the mandrel; and
- wherein the data acquisition system enables contemporaneous review of pore fluid pressure data.
14. (Original) The apparatus of claim 13, wherein the measurement data from each of the means for measuring is converted to digital signals, multiplexed, and then relayed to the data acquisition system.

Serial No. 10/693,624  
Docket No. 062004-1791

15. (Canceled)

16. (Currently Amended) The method of claim ~~15~~ 17, wherein collecting attachment module measurements is performed by at least one individual load cell, the load cell including a friction sleeve that measures an interface resistance, the interface resistance corresponding to interface strength.

17. (Previously Presented) A method of determining in situ pore fluid and soil properties, the method comprising the steps of:

positioning a penetrating tip member so as to penetrate into the soil at a particular subsurface area;

positioning an attachment module in a predetermined relationship to the penetrating tip member to form a penetrometer;

forcing the penetrometer into the soil beginning with the penetrating tip member; and

collecting attachment module measurements from at least one piezo sensor coupled to at least one mandrel, wherein the piezo sensor obtains an in situ measurement of pore fluid pressure at a depth that corresponds to the location of the at least one mandrel, wherein collecting attachment module measurements from a plurality of load cells comprises providing each of the load cells a corresponding plurality of mandrels and friction sleeves, the plurality of friction sleeves being configured to be removable, such that the arrangement of the friction sleeves along the attachment module portion of the penetrometer may be reconfigured into different order arrangements for measuring corresponding interface resistances of the friction sleeves.

18. (Previously Presented) The method of claim 16, wherein collecting attachment module measurements from a plurality of load cells comprises each individual load cell with a friction sleeve configured with a surface texture, the surface texture of select friction sleeves being configured with a diamond-shaped pattern so as to induce internal shearing of the soil around the penetrometer as the penetrometer is penetrated into the soil.

Serial No. 10/693,624  
Docket No. 062004-1791

19. (Previously Presented) The method of claim 16, wherein collecting attachment module measurements from a plurality of individual load cells comprises arranging a plurality of friction sleeves, wherein the friction sleeves are arranged in ascending order of vertically according to increasing roughness of the surface texture, such that the least rough friction sleeve is placed closest to the penetrating tip member and the roughest friction sleeve is placed furthest away from the penetrating tip member.
20. (Currently Amended) The method of claim 45 17, further including the steps of:
- measuring penetration depth of the penetrometer;
  - measuring penetration tip member values;
  - measuring verticality of the penetrating tip member, where the penetration depth, penetration tip member values, and verticality measurements comprise the drive tip measurements; and
  - measuring pore fluid pressure at each measurement increment on each piezo sensors located in the mandrel.
21. (Original) The method of claim 20, further comprising converting analog measurement data from each of the measurements to digital signals, multiplexing, and then relaying the multiplexed data to the data acquisition system.
22. (Previously Presented) The method of claim 16, further comprising isolating the piezo sensor to measure the pore fluid pressure generated for each load cell, wherein the friction sleeve of each load cell induces an internal shearing of the soil, wherein the piezo sensor measures the pore fluid pressure induced by each friction sleeve of the individual load cells at a particular subsurface.
23. (Currently amended) The method of claim 45 17, further comprising collecting penetrating tip measurements.

Serial No. 10/693,624  
Docket No. 062004-1791

24. (Currently amended) An apparatus for determining in situ pore fluid and soil properties, the apparatus comprising:

a penetrating tip member configured to penetrate the soil; and

an attachment module coupled to the penetrating tip member, the attachment module including at least one mandrel, each mandrel including at least one piezo sensor and a friction sleeve,

each friction sleeve of the respective mandrel having surface texture of a particular roughness that is capable of inducing an internal shearing of the soil, each piezo sensor of the respective mandrel being capable of measuring in situ pore fluid pressure from the induced shearing of the soil generated by the friction sleeve of the respective mandrel mandrel,

wherein the attachment module includes multiple mandrels, each mandrel having at least one piezo sensor and a friction sleeve configured with a surface texture, the attachment module further comprising a vertical arrangement of the friction sleeves.

25. (Canceled)

26. (Currently Amended) The apparatus of claim ~~25~~ 24, wherein the at least one mandrel comprises a leading mandrel and a trailing mandrel, a leading piezo sensor of the leading mandrel being capable of measuring the pore fluid pressure generated from a leading friction sleeve of the leading mandrel and the penetrating tip member,

wherein a trailing piezo sensor of the trailing mandrel measures the pore fluid pressure generated from a trailing friction sleeve of the trailing mandrel, the leading friction sleeve and the penetrating tip member.

27. (Previously Presented) The apparatus of claim 26, wherein the measurement of the pore fluid pressure generated from the trailing friction sleeve is calculated by subtracting the measurements of the leading piezo sensor from the trailing piezo sensor.